

JG1B50P120FG2

Product Preview

**1200V/50A PIM WITH
FIELD-STOP TRENCH IGBT, DIODE AND NTC**

Features


- Low $V_{CE(sat)}$
- Fast Switching
- High Ruggedness
- Short-Circuit Rated



| Product Summary | |
|-------------------|-----------------------------------|
| V_{CES} | 1200V |
| I_C | 50A |
| $V_{CE(sat),typ}$ | 1.7V ($T_J = 25^\circ\text{C}$) |

Applications

- General Purpose Inverters
- Frequency Converters
- Industrial Motor Drives
- Servos


Internal Connection


- **IGBT, Inverter**

Absolute Maximum Ratings

| Parameter | Symbol | Limit | Unit |
|---|-----------|----------|------|
| Collector-to-Emitter Voltage | V_{CES} | 1200 | V |
| Gate-to-Emitter Voltage | V_{GES} | ± 20 | |
| Continuous DC Collector Current ($T_c = 100^\circ\text{C}$, $T_J = 175^\circ\text{C}$) | I_{CDC} | 50 | A |
| Repetitive Peak Collector Current ($t_p=1\text{ms}$) | I_{CRM} | 100 | |

Electrical Characteristics ^{(1), (2)}

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|---|---------------|---|------|------|-----|------|
| Collector-to-Emitter Breakdown Voltage | BV_{CES} | $V_{GE} = 0V, I_C = 250\mu A$ | 1200 | - | - | V |
| Collector-to-Emitter Leakage Current | I_{CES} | $V_{CE} = 1200V, V_{GE} = 0V$ | - | - | 1 | mA |
| Gate-to-Emitter Leakage Current | I_{GES} | $V_{CE} = 0V, V_{GE} = \pm 20V$ | - | - | 100 | nA |
| Gate Threshold Voltage | $V_{GE(th)}$ | $V_{CE} = V_{GE}, I_C = 1.5mA$ | 5.5 | 6.5 | 7.5 | V |
| Collector-to-Emitter Saturation Voltage | $V_{CE(sat)}$ | $V_{GE} = 15V, I_C = 50A$ | - | 1.7 | 2.0 | |
| | | $V_{GE} = 15V, I_C = 50A,$ $T_J = 125^\circ C$ | - | 2.05 | - | |
| | | $V_{GE} = 15V, I_C = 50A,$ $T_J = 150^\circ C$ | - | 2.15 | - | |
| Total Gate Charge | Q_g | $V_{CC} = 600V,$ $V_{GE} = 15V,$ $I_C = 50A$ | - | 220 | - | nC |
| Input Capacitance | C_{iss} | $V_{CE} = 25V,$ $V_{GE} = 0V,$ $f = 1MHz$ | - | 4150 | - | pF |
| Output Capacitance | C_{oss} | | - | 230 | - | |
| Reverse Transfer Capacitance | C_{rss} | | - | 54 | - | |
| Turn-on Delay time | $t_{d(ON)}$ | $V_{CC} = 600V,$ $V_{GE} = 0/15V,$ $R_G = 10\Omega,$ $I_C = 50A,$ $L_{load} = 0.82mH,$ Energy losses include "tail" and diode reverse recovery. | - | 84 | - | ns |
| Rise Time | t_r | | - | 88 | - | |
| Turn-off Delay time | $t_{d(OFF)}$ | | - | 360 | - | |
| Fall Time | t_f | | - | 103 | - | |
| Turn-On Switching Loss | E_{on} | | - | 4.8 | - | mJ |
| Turn-Off Switching Loss | E_{off} | | - | 2.4 | - | |
| IGBT Total Switching Loss | E_{ts} | | - | 7.2 | - | |
| Turn-on Delay time | $t_{d(ON)}$ | $V_{CC} = 600V,$ $V_{GE} = 0/15V,$ $R_G = 10\Omega,$ $I_C = 50A,$ $L_{load} = 0.82mH,$ Energy losses include "tail" and diode reverse recovery. $T_J = 150^\circ C$ | - | 85 | - | ns |
| Rise Time | t_r | | - | 100 | - | |
| Turn-off Delay time | $t_{d(OFF)}$ | | - | 420 | - | |
| Fall Time | t_f | | - | 160 | - | |
| Turn-On Switching Loss | E_{on} | | - | 7.3 | - | mJ |
| Turn-Off Switching Loss | E_{off} | | - | 3.5 | - | |
| IGBT Total Switching Loss | E_{ts} | | - | 10.8 | - | |
| Short Circuit Collector Current | $I_{C(SC)}$ | $V_{GE} = 15V,$ $V_{CC} \leq 600V,$ $t_{SC} \leq 10\mu s$ | - | 195 | - | A |

- **Diode, Inverter**

Absolute Maximum Ratings

| Parameter | Symbol | Limit | Unit |
|---|-----------|-------|------|
| Repetitive Peak Reverse Voltage | V_{RRM} | 1200 | V |
| Continuous DC Forward Current ($T_c = 100\text{ }^\circ\text{C}$, $T_j = 150\text{ }^\circ\text{C}$) | I_F | 50 | A |
| Repetitive Peak Forward Current ($t_p=1\text{ms}$) | I_{FRM} | 100 | |

Electrical Characteristics ⁽¹⁾

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-------------------------------------|-----------|---|-----|------|------|---------------|
| Diode Forward Voltage | V_F | $I_F = 50\text{A}$ | - | 2.0 | 2.45 | V |
| | | $I_F = 50\text{A}$ $T_j = 125\text{ }^\circ\text{C}$ | - | 1.75 | - | |
| | | $I_F = 50\text{A}$ $T_j = 150\text{ }^\circ\text{C}$ | - | 1.7 | - | |
| Diode Reverse-Recovery Charge | Q_{rr} | $V_R = 600\text{V}$, $I_F = 50\text{A}$, $di_F/dt = -450\text{ A}/\mu\text{s}$ | - | 1.86 | - | μC |
| Diode Peak Reverse-Recovery Current | I_{rrm} | | - | 16.5 | - | A |
| Diode Reverse-Recovery Loss | E_{rr} | | - | 0.55 | - | mJ |

- **IGBT, Brake-Chopper**

Absolute Maximum Ratings

| Parameter | Symbol | Limit | Unit |
|---|-----------|----------|------|
| Collector-to-Emitter Voltage | V_{CES} | 1200 | V |
| Gate-to-Emitter Voltage | V_{GES} | ± 20 | |
| Continuous DC Collector Current ($T_c = 100\text{ }^\circ\text{C}$, $T_j = 175\text{ }^\circ\text{C}$) | I_{CDC} | 35 | A |
| Repetitive Peak Collector Current ($t_p=1\text{ms}$) | I_{CRM} | 70 | |

Electrical Characteristics ^{(1), (2)}

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|--|--------------|--|------|-----|-----|------|
| Collector-to-Emitter Breakdown Voltage | BV_{CES} | $V_{GE} = 0\text{V}$, $I_C = 250\mu\text{A}$ | 1200 | - | - | V |
| Collector-to-Emitter Leakage Current | I_{CES} | $V_{CE} = 1200\text{V}$, $V_{GE} = 0\text{V}$ | - | - | 1 | mA |
| Gate-to-Emitter Leakage Current | I_{GES} | $V_{CE} = 0\text{V}$, $V_{GE} = \pm 20\text{V}$ | - | - | 100 | nA |
| Gate Threshold Voltage | $V_{GE(th)}$ | $V_{CE} = V_{GE}$, $I_C = 1.5\text{mA}$ | 5.5 | 6.5 | 7.5 | V |

| | | | | | | |
|---|---------------|---|------|------|-----|----|
| Collector-to-Emitter Saturation Voltage | $V_{CE(sat)}$ | $V_{GE} = 15V, I_C = 35A$ | - | 1.65 | 2.0 | |
| | | $V_{GE} = 15V, I_C = 35A, T_J = 125^\circ C$ | - | 2.0 | - | |
| | | $V_{GE} = 15V, I_C = 35A, T_J = 150^\circ C$ | - | 2.15 | - | |
| Total Gate Charge | Q_g | $V_{CC} = 600V, V_{GE} = 15V, I_C = 35A$ | - | 148 | - | nC |
| Input Capacitance | C_{iss} | $V_{CE} = 25V, V_{GE} = 0V, f = 1MHz$ | - | 3460 | - | pF |
| Output Capacitance | C_{oss} | | - | 154 | - | |
| Reverse Transfer Capacitance | C_{rss} | | - | 41 | - | |
| Turn-on Delay time | $t_{d(ON)}$ | $V_{CC} = 600V, V_{GE} = 0/15V, R_G = 10\Omega, I_C = 35A, L_{load} = 0.82mH,$ Energy losses include "tail" and diode reverse recovery. | - | 55 | - | ns |
| Rise Time | t_r | | - | 58 | - | |
| Turn-off Delay time | $t_{d(OFF)}$ | | - | 300 | - | |
| Fall Time | t_f | | - | 110 | - | |
| Turn-On Switching Loss | E_{on} | $V_{CC} = 600V, V_{GE} = 0/15V, R_G = 10\Omega, I_C = 35A, L_{load} = 0.82mH,$ Energy losses include "tail" and diode reverse recovery. $T_J = 150^\circ C$ | - | 2.8 | - | mJ |
| Turn-Off Switching Loss | E_{off} | | - | 1.6 | - | |
| IGBT Total Switching Loss | E_{ts} | | - | 4.4 | - | |
| Turn-on Delay time | $t_{d(ON)}$ | | - | 57 | - | |
| Rise Time | t_r | $V_{CC} = 600V, V_{GE} = 0/15V, R_G = 10\Omega, I_C = 35A, L_{load} = 0.82mH,$ Energy losses include "tail" and diode reverse recovery. $T_J = 150^\circ C$ | - | 60 | - | ns |
| Turn-off Delay time | $t_{d(OFF)}$ | | - | 320 | - | |
| Fall Time | t_f | | - | 136 | - | |
| Turn-On Switching Loss | E_{on} | | - | 4.95 | - | |
| Turn-Off Switching Loss | E_{off} | - | 2.15 | - | mJ | |
| IGBT Total Switching Loss | E_{ts} | - | 7.1 | - | | |

- **Diode, Brake-Chopper**

Absolute Maximum Ratings

| Parameter | Symbol | Limit | Unit |
|--|-----------|-------|------|
| Repetitive Peak Reverse Voltage | V_{RRM} | 1200 | V |
| Continuous DC Forward Current ($T_c = 100^\circ C, T_J = 150^\circ C$) | I_F | 15 | A |
| Repetitive Peak Forward Current ($t_p=1ms$) | I_{FRM} | 30 | |

Electrical Characteristics ⁽¹⁾

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-------------------------------------|-----------|--|-----|------|------|---------|
| Diode Forward Voltage | V_F | $I_F = 15A$ | - | 2.0 | 2.40 | V |
| | | $I_F = 15A$ $T_J = 125^\circ C$ | - | 1.75 | - | |
| | | $I_F = 15A$ $T_J = 150^\circ C$ | - | 1.65 | - | |
| Diode Reverse-Recovery Charge | Q_{rr} | $V_R = 600V, I_F = 15A,$ $dI_F/dt = -600 A/\mu s$ | - | 1.2 | - | μC |
| Diode Peak Reverse-Recovery Current | I_{rrm} | | - | 14.5 | - | A |
| Diode Reverse-Recovery Loss | E_{rr} | | - | 0.4 | - | mJ |

- **Diode, Rectifier**

Absolute Maximum Ratings ⁽¹⁾

| Parameter | Symbol | Limit | Unit |
|--|-------------|-------|--------|
| Repetitive Peak Reverse Voltage | V_{RRM} | 1600 | V |
| Average Output Current 50/60Hz,sine wave ($T_c = 100^\circ C$) | $I_{F(AV)}$ | 35 | A |
| Maximum RMS Current at Rectifier Output ($T_c = 100^\circ C$) | I_{RMSM} | 60 | |
| Surge Forward Current ($V_R=0, t_p=10ms$) | I_{FSM} | 320 | |
| I^2t – value ($V_R=0, t_p = 10 ms$) | I^2t | 510 | A^2s |

Electrical Characteristics

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-----------------------|--------|--------------------------------------|-----|------|-----|------|
| Diode Forward Voltage | V_F | $I_F = 35A$ $T_J = 150^\circ C$ | - | 1.12 | - | V |
| Diode Reverse Current | I_R | $V_R = 1600V$ $T_J = 150^\circ C$ | - | - | 2.0 | mA |

- **NTC thermistors**

Characteristics

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-------------------|--------------|---|-----|------|-----|------------|
| Rated Resistance | R_{25} | | - | 5.0 | - | k Ω |
| Deviation of R100 | $\Delta R/R$ | $T_c = 100^\circ C$ $R_{100} = 493.3\Omega$ | -5 | - | 5 | % |
| Power Dissipation | P_{25} | | - | 20.0 | - | mW |
| B-value | $B_{25/50}$ | $R_2 = R_{25} \exp [B_{25/50}(1/T_2 - 1/(298.15 K))]$ | - | 3375 | - | K |

- **Module**

Absolute Maximum Ratings

| Parameter | Symbol | Limit | Unit |
|---|--------------|-------------|------|
| Maximum Junction Temperature | T_j | -40 to +175 | °C |
| Operating Junction Temperature | $T_{vj\ op}$ | -40 to +150 | |
| Storage Temperature | T_{stg} | -40 to +150 | |
| Isolation Voltage (f = 50 Hz, t = 1 min) | V_{iso} | 2.5 | kV |

Characteristics

| Parameter | Symbol | Min | Typ | Max | Unit |
|---|-----------------|-----|-------|-----|------|
| Stray Inductance-module | L_{SCE} | - | 30 | - | nH |
| Module Lead Resistance, Terminal to Chip | $R_{CC'+EE'}$ | - | 5.0 | - | mΩ |
| Module Lead Resistance, Terminal to Chip | $R_{AA'+CC'}$ | - | 6.0 | - | |
| Junction-to-Case Thermal Resistance, per IGBT, Inverter | $R_{\theta JC}$ | - | 0.48 | | °C/W |
| Junction-to-Case Thermal Resistance, per Diode, Inverter | | - | 0.75 | | |
| Junction-to-Case Thermal Resistance, per IGBT, Brake-Chopper | | - | 0.6 | | |
| Junction-to-Case Thermal Resistance, per Diode, Brake-Chopper | | - | 1.30 | | |
| Junction-to-Case Thermal Resistance, per Diode, Rectifier | | - | 0.90 | | |
| Case-to-Heatsink Thermal Resistance, per IGBT, Inverter | $R_{\theta CH}$ | - | 0.6 | - | °C/W |
| Case-to-Heatsink Thermal Resistance, per Diode, Inverter | | - | 0.75 | - | |
| Case-to-Heatsink Thermal Resistance, per IGBT, Brake-Chopper | | - | 0.6 | - | |
| Case-to-Heatsink Thermal Resistance, per Diode, Brake-Chopper | | - | 1.05 | - | |
| Case-to-Heatsink Thermal Resistance, per Diode, Rectifier | | - | 0.95 | - | |
| Case-to-Heatsink Thermal Resistance, per Module | | - | 0.037 | - | |
| Mounting Force per Clamp | F | 30 | - | 80 | N |
| Weight per Module | G | - | 45 | - | g |

(1) $T_j = 25^\circ\text{C}$ unless otherwise specified

(2) t_r : from 10% of I_c to 90% of I_c ; t_f : from 90% of I_c to 10% of I_c ;

E_{on} : from 10% of V_{GE} to 10% of V_{CE} ; E_{off} : from 90% of V_{GE} to 10% of I_c .

• Typical Electrical Characteristics




Fig. 1 IGBT (Inverter) Output Characteristics




Fig. 2 IGBT (Inverter) Transfer Characteristics




Fig. 3 IGBT (Inverter) Switching Loss vs. Ic




Fig. 4 IGBT (Inverter) Switching Loss vs. Rg




Fig. 5 RBSOA




Fig. 6 IGBT (Inverter) Transient Thermal Impedance




Fig. 7 Diode (Inverter) Forward Characteristics




Fig. 8 Diode (Inverter) Switching Loss (Erec) vs. If




Fig. 9 Diode (Inverter) Reverse-Recovery Loss vs. Rg




Fig. 10 IGBT (Break-Chopper) Output Characteristics




Fig. 11 Diode (Brake-Chopper) Output Characteristics






Fig. 12 NTC Temperature Characteristics

• **Circuit diagram**



• **Package Dimensions**



Revision history of JG1B50P120FG2 Specification

| Version | Change Items | Effective Date |
|----------------|---------------------|-----------------------|
| 1.00 | Initial Release | Jan 2021 |

Notice

General – This document contains information on a product under development. Information in this document is believed to be accurate and reliable. However, JSAB Technologies does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes – JSAB Technologies reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use – JSAB Technologies' products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an JSAB Technologies product can reasonably be expected to result in personal injury, death or severe property or environmental damage. JSAB Technologies accepts no liability for inclusion and/or use of JSAB Technologies' products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications – Applications that are described herein for any of these products are for illustrative purposes only. JSAB Technologies makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values – Stress above one or more limiting values may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale – JSAB Technologies' products are sold subject to the general terms and conditions of commercial sale, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by JSAB Technologies. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license – Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control – This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Quick reference data – The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.