

JHH50N120HA3

Product Preview

**1200V/50A HIGH SPEED FIELD-STOP TRENCH IGBT
WITH DIODE**

Features



- High Speed Switching
- Low $V_{CE(sat)}$
- High Ruggedness


Product Summary

| | |
|-------------------|-----------------------------------|
| V_{CES} | 1200V |
| I_C | 50A ⁽¹⁾ |
| $V_{CE(sat),typ}$ | 1.7V ($T_J = 25^\circ\text{C}$) |
| Package | TO-247 |

Applications

- High Frequency Converters
- Uninterrupted Power Supply
- Solar Inverters
- Welding


Ordering Information

| Part Number | Marking | Package | Packaging |
|--------------|-------------|---------|-----------|
| JHH50N120HA3 | HH50N120HA3 | TO-247 | Tube |

Absolute Maximum Ratings

| Parameter | Symbol | Limit | Unit |
|--|--------------|-------------|------|
| Collector-to-Emitter Voltage | V_{CES} | 1200 | V |
| Gate-to-Emitter Voltage | V_{GES} | ± 20 | |
| DC Collector Current ($T_c = 25^\circ\text{C}$, $T_J = 175^\circ\text{C}$) | I_C | 85 | A |
| DC Collector Current ($T_c = 90^\circ\text{C}$, $T_J = 175^\circ\text{C}$) | | 59 | |
| Pulsed Collector Current (pulse width limited by maximum T_J) | I_{CM} | 200 | |
| Diode Forward Current ($T_c = 25^\circ\text{C}$, $T_J = 175^\circ\text{C}$) | I_F | 65 | |
| Diode Forward Current ($T_c = 90^\circ\text{C}$, $T_J = 175^\circ\text{C}$) | | 44 | |
| Diode Pulsed Current (pulse width limited by maximum T_J) | I_{FM} | 200 | |
| Maximum Power Dissipation ($T_c = 25^\circ\text{C}$, $T_J = 175^\circ\text{C}$) | $P_{D(max)}$ | 333 | W |
| Maximum Junction Temperature | T_{J_max} | 175 | °C |
| Operating Junction Temperature | T_{J_op} | -40 to +175 | |
| Storage Temperature | T_{stg} | -55 to +150 | |
| Maximum Lead Temperature for Soldering (1/8" from case for 5 seconds) | T_{slid} | 260 | |

Static Electrical Characteristics ⁽²⁾

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|---|---------------|---|------|------|------|---------|
| Collector-to-Emitter Breakdown Voltage | BV_{CES} | $V_{GE} = 0V, I_C = 250\mu A$ | 1200 | - | - | V |
| Collector-to-Emitter Leakage Current | I_{CES} | $V_{CE} = 1200V, V_{GE} = 0V$ | - | - | 10 | μA |
| | | $V_{CE} = 1200V, V_{GE} = 0V,$ $T_J = 150^\circ C$ | - | - | 5 | mA |
| | | $V_{CE} = 1200V, V_{GE} = 0V,$ $T_J = 175^\circ C$ | - | - | 20 | mA |
| Gate-to-Emitter Leakage Current | I_{GES} | $V_{CE} = 0V, V_{GE} = \pm 20V$ | - | - | 100 | nA |
| Gate Threshold Voltage | $V_{GE(th)}$ | $V_{CE} = V_{GE}, I_C = 1mA$ | 4.2 | 5.2 | 6.2 | V |
| Collector-to-Emitter Saturation Voltage | $V_{CE(sat)}$ | $V_{GE} = 15V, I_C = 50A$ | - | 1.7 | 2 | |
| | | $V_{GE} = 15V, I_C = 50A,$ $T_J = 150^\circ C$ | - | 2.3 | - | |
| | | $V_{GE} = 15V, I_C = 50A,$ $T_J = 175^\circ C$ | - | 2.5 | - | |
| Diode Forward Voltage | V_F | $V_{GE} = 0V, I_F = 50A$ | - | 2.3 | 2.75 | |
| | | $V_{GE} = 0V, I_F = 50A$ $T_J = 150^\circ C$ | - | 2 | - | |
| | | $V_{GE} = 0V, I_F = 50A$ $T_J = 175^\circ C$ | - | 1.95 | - | |

Thermal Characteristics

| Parameter | Symbol | Min | Typ | Max | Unit |
|--|-----------------|-----|-----|------|--------------|
| Junction-to-Ambient Thermal Resistance | $R_{\theta JA}$ | - | - | 40 | $^\circ C/W$ |
| Junction-to-Case Thermal Resistance, IGBT | $R_{\theta IC}$ | - | - | 0.45 | |
| Junction-to-Case Thermal Resistance, Diode | | - | - | 0.88 | |

Dynamic Electrical Characteristics (2)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|------------------------------|-----------|--|-----|------|-----|------|
| Total Gate Charge | Q_g | $V_{CC} = 600V,$ $V_{GE} = 15V,$ $I_C = 50A$ | - | 200 | - | nC |
| Input Capacitance | C_{iss} | $V_{CE} = 25V,$ $V_{GE} = 0V,$ $f = 1MHz$ | - | 4029 | - | pF |
| Output Capacitance | C_{oss} | | - | 127 | - | |
| Reverse Transfer Capacitance | C_{rss} | | - | 40 | - | |

Switching Characteristics, Inductive Load (2), (3)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-------------------------------------|--------------|--|-----|------|-----|------|
| Turn-on Delay time | $t_{d(ON)}$ | $V_{CC} = 600V,$ $V_{GE} = 0/15V,$ $R_G = 10\Omega,$ $I_C = 50A,$ $L_{load} = 0.82mH,$ Energy losses include "tail" and diode reverse recovery. | - | 43 | - | ns |
| Rise Time | t_r | | - | 54 | - | |
| Turn-off Delay time | $t_{d(OFF)}$ | | - | 202 | - | |
| Fall Time | t_f | | - | 69 | - | |
| Turn-On Switching Loss | E_{on} | | - | 3.4 | - | mJ |
| Turn-Off Switching Loss | E_{off} | | - | 1.35 | - | |
| IGBT Total Switching Loss | E_{ts} | | - | 4.75 | - | |
| Diode Reverse-Recovery Time | t_{rr} | $V_R = 600V,$ $I_F = 50A,$ $dI_F/dt = -740 A/\mu s$ | - | 240 | - | ns |
| Diode Reverse-Recovery Charge | Q_{rr} | | - | 2540 | - | nC |
| Diode Peak Reverse-Recovery Current | I_{rrm} | | - | 29 | - | A |

(1) $T_c = 105^\circ C, T_j = 175^\circ C.$

(2) $T_j = 25^\circ C$ unless otherwise specified

(3) t_r : from 10% of I_C to 90% of I_C ; t_f : from 90% of I_C to 10% of I_C ;

E_{on} : from 10% of V_{GE} to 10% of V_{CE} ; E_{off} : from 90% of V_{GE} to 10% of I_C .

Typical Electrical Characteristics




Fig. 1 Typical output characteristics

($T_J = 25\text{ }^\circ\text{C}$, $t_p = 250\text{ }\mu\text{s}$)




Fig. 2 Typical output characteristics

($T_J = 175\text{ }^\circ\text{C}$, $t_p = 250\text{ }\mu\text{s}$)




Fig. 3 Typical transfer characteristics

($V_{CE} = 20\text{ V}$, $t_p = 250\text{ }\mu\text{s}$)




Fig. 4 Typical gate threshold voltage as a function of junction temperature

($V_{CE} = V_{GE}$, $I_C = 1\text{ mA}$)




Fig. 5 Typical saturation voltage characteristics
($V_{GE} = 15\text{ V}$, $t_p = 250\ \mu\text{s}$)




Fig. 6 Typical saturation voltage as a function of junction temperature
($V_{GE} = 15\text{ V}$, $t_p = 250\ \mu\text{s}$)




Fig. 7 Maximum DC collector current as a function of case temperature




Fig. 8 Typical gate charge characteristics




Fig. 9 Typical capacitance as a function of collector-to-emitter voltage




Fig. 10 Typical diode forward current as a function of forward voltage
 $(V_{GE} = 0V, t_p = 250 \mu s)$





Fig. 11 Typical diode forward voltage as a function of junction temperature

Package Drawing



| SYM | MILLIMETERS | | INCHES | |
|----------|-------------|-------|----------|------|
| | MIN | MAX | MIN | MAX |
| A | 4.83 | 5.21 | .190 | .205 |
| A1 | 2.29 | 2.54 | .090 | .100 |
| A2 | 1.91 | 2.16 | .075 | .085 |
| b' | 1.07 | 1.28 | .042 | .050 |
| b | 1.07 | 1.33 | .042 | .052 |
| b1 | 1.91 | 2.41 | .075 | .095 |
| b2 | 1.91 | 2.16 | .075 | .085 |
| b3 | 2.87 | 3.38 | .113 | .133 |
| b4 | 2.87 | 3.13 | .113 | .123 |
| c' | 0.55 | 0.65 | .022 | .026 |
| c | 0.55 | 0.68 | .022 | .027 |
| D | 20.80 | 21.10 | .819 | .831 |
| D1 | 16.25 | 17.65 | .640 | .695 |
| D2 | 0.95 | 1.25 | .037 | .049 |
| E | 15.75 | 16.13 | .620 | .635 |
| E1 | 13.10 | 14.15 | .516 | .557 |
| E2 | 3.68 | 5.10 | .145 | .201 |
| E3 | 1.00 | 1.90 | .039 | .075 |
| E4 | 12.38 | 13.43 | .487 | .529 |
| e | 5.44 BSC | | .214 BSC | |
| N | 3 | | 3 | |
| L | 19.81 | 20.32 | .780 | .800 |
| L1 | 4.10 | 4.40 | .161 | .173 |
| ϕP | 3.51 | 3.65 | .138 | .144 |
| Q | 5.49 | 6.00 | .216 | .236 |
| S | 6.04 | 6.30 | .238 | .248 |
| T | 17.5° REF. | | | |
| W | 3.5° REF. | | | |
| X | 4° REF. | | | |

TO-247

Notice

General – This document contains information on a product under development. Information in this document is believed to be accurate and reliable. However, JSAB Technologies does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes – JSAB Technologies reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use – JSAB Technologies' products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an JSAB Technologies product can reasonably be expected to result in personal injury, death or severe property or environmental damage. JSAB Technologies accepts no liability for inclusion and/or use of JSAB Technologies' products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications – Applications that are described herein for any of these products are for illustrative purposes only. JSAB Technologies makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values – Stress above one or more limiting values may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale – JSAB Technologies' products are sold subject to the general terms and conditions of commercial sale, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by JSAB Technologies. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license – Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control – This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Quick reference data – The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.